NRCTAPES

TECHNICAL DATA SHEET Carry Handle Tape 51M

Product

This carry handle tape is developed for the usage to carry shrink wrapped Packages/multipacks up to 12kg in combination with an integrated (printed) MOPP foam carry handle for manual, semi-automatic and automatic packaging lines.

| Technical DataCarrierAdhesiveThickness carrierTotal thicknessAdhesion on PEAdhesion on steelTensile strengthElongationColor tapeInsertPrinting | MOPP (mono oriented polypropylene) Solvent free hotmelt 51 micron 69 micron 7.3 (N/25mm) 10.0 (N/25mm) > 360 (N/25mm) > 35% transparent MOPP foam 120 micron neutral or printed 1 to 6 colors |
|--|---|
|--|---|

Dimensions

Supplied in flat rolls or spools

| | | | | Pallet |
|-------|---------|--------------|------------------------------|--------|
| Width | Length | Core | Packaging | weight |
| | | | | Apprx |
| 25mm | 330mtr | 3 inch 25mm | 12 rolls/box 48 boxes/pallet | 730kg |
| | | | | Apprx |
| 25mm | 3000mtr | 6 inch 180mm | 1 roll/box 48 boxes/pallet | 510kg |
| | | | | Apprx |
| 25mm | 3500mtr | 6 inch 180mm | 1 roll/box 48 boxes/pallet | 590kg |
| | | | | Apprx |
| 25mm | 5000mtr | 6 inch 350mm | 1 roll/box 24 boxes/pallet | 490kg |

Other dimensions upon request.

Conditions
 Please store in a dry place away from sunlight and direct heat sources. Ideal Storage conditions 10 Celsius – 40 Celsius. If conditions are respected, the tape has a 12 month guarantee.
 Disclaimer
 The above mentioned data are to be considered as reference data based on our experience in the production of the handles and are not a warranty for the results of the application. Therefore each single application should be tested in advance. Neither seller or manufacturer shall be reliable for any loss and damage – direct, incidental or consequential – arising from the use of the product.
 C a r r y h a n d l e t a p e