



TECHNICAL DATA SHEET - Carry Handle Tape 51H

Product This carry handle tape is developed for the usage to carry shrink wrapped Packages/multipacks up to 12kg in combination with a cardboard insert for manual, semi-automatic and automatic packaging lines.

Technical Data

Carrier	: MOPP (mono oriented polypropylene)
Adhesive	: Solvent free hotmelt
Thickness carrier	: 50 micron
Total thickness	: 70 micron
Adhesion on PE	: 5.0 (N/25mm)
Adhesion on steel	: 10.0 (N/25mm)
Tensile strength	: 350 (N/25mm)
Elongation	: 30%
Colour	: transparent

Dimensions Supplied in flat rolls or spools

Width	Length	Core	Packaging	Pallet weight
25mm	660mtr	3 inch 25mm	12 rolls/box 48 boxes/pallet	Apprx 660kg
25mm	5000mtr	6 inch 180mm	1 roll/box 48 boxes/pallet	Apprx 480kg
25mm	7000mtr	6 inch 180mm	1 roll/box 48 boxes/pallet	Apprx 610kg

Other dimensions upon request.

Conditions Please store in a dry place away from sunlight and direct heat sources. Ideal Storage conditions 10 Celsius – 40 Celsius. If conditions are respected, the tape has a 12 month guarantee.

Disclaimer The above mentioned data are to be considered as reference data based on our experience in the production of the handles and are not a warranty for the results of the application. Therefore each single application should be tested in advance. Neither seller or manufacturer shall be reliable for any loss and damage – direct, incidental or consequential – arising from the use of the product.